



Rope Pear Socket Nemag

General: The Nemag Rope Pear Socket is designed to, in combination with the Nemag Quick Release Link, smoothly pass over cable sheaves. The life span of the Nemag Rope Pear Socket generally surpasses that of the steel wire rope. The Rope Pear socket can be fitted by casting with a 2-component casting mass without the need for outside assistance, and ensures a strong connection. Nemag Rope Pear Sockets are suited to any type of steel wire rope.

Material: High grade casted steel.

Marking: Manufacturers mark, size and batch number.

Important: *The specified capacities shown are for grab operation. For other applications, use safety factor of 5.*



Ask quote

Technical support

Art No	Stock Code	Pear size	Rope Ø mm	WLL tons*	MBL tons	A	B	C	D	E mm	F	G	H	I	Weight kg
10.10NRPS01		1	10-11	1,5	10	81	48	22	195	12	11,5	20	24	12	0,4
10.10NRPS02		2	12-13	2	14	95	56	25	195	15,5	13,5	22	25	14	0,5
10.10NRPS03		3	14-15	2,5	17,5	109	64	28	220	17,5	15,5	24	29	16	0,6
10.10NRPS04		4	16-17	3	22,5	123	70	31	220	19,5	17,5	26	31	18	0,9
10.10NRPS05		5	18-19	4,5	27,5	135	84	33	245	21	19	30	42	20	1,3
10.10NRPS06		6	20-21	5	35	152	84	36	310	23	21	33	38	23	1,7
10.10NRPS07		7	22-24	7	42,5	166	100	40	310	26	23	37	48	26	2,3
10.10NRPS08		8	25-27	8	52,5	186	100	43	350	28	25	39	44	29	3,2
10.10NRPS09		9	28-30	11	70	202	120	45	350	31	27	40	58	32	4,1
10.10NRPS10		10	31-33	13	85	222	120	52	445	32	28,5	45	56	35	5,2
10.10NRPS11	04A0503	11	34-36	15	95	239	142	55	445	36	31,5	50	70	40	6,4
10.10NRPS12		12	37-39	17	110	264	142	60	495	39	34,5	51	64	41	7,9
10.10NRPS13	04A0510	13	40-42	21	125	285	166	63	555	43	36,5	59	80	44	9,5
10.10NRPS14	04A0513	14	43-45	26	155	312	166	68	595	47	40	62	72	48	11,2
10.10NRPS15		15	46-48	30	180	337	170	75	595	51	44	66	68	53	13,0
10.10NRPS17		17	52-56	42,5	240	400	220	84	880	60	54	75	90	59	23,0

* Working load is max. working load for grabbing operations. For other operations apply the min. safety factor 5.

