

External Gear Pumps

F, N, & G Series

RA 10 097/02.06
Replaces 11.04

1/96



Fixed displacement pumps
Sizes 4.0...63 cm³ (.25...3.84 in³)

Contents

Product Overview	4
Installation	7
Drive Arrangements	8
Multiple Gear Pumps	11
Pumps with Integral Valves	13
F-Series External Gear Pump	
- Ordering Code	14
- Product Index	15
- Drive Shafts	16
- Front Cover	17
- Port Connections	18
- Performance Ratings	19
- SAE O-Ring BOSS - Standard Porting	19
- SAE Porting-Specifications & Dimensions	19
- Performance Curves	20
- Drawings and Charts	23
N-Series External Gear Pump	
- Ordering Code	44
- Product Index	45
- Performance Ratings	46
- SAE O-Ring BOSS - Standard Porting	46
- SAE Porting-Specifications & Dimensions	46
- Performance Curves	47
- Drawings and Charts	49

Page

Contents

G-Series External Gear Pump	68
- Ordering Code	68
- Product Index	69
- Performance Ratings	70
- SAE O-Ring BOSS - Standard Porting	70
- SAE Porting-Specifications & Dimensions	70
- Performance Curves	71
- Drawings and Charts	73
Multiple Pump Arrangements	
- Ordering Code	80
- Drawing Index	81
- Drawing and Charts	82
Seal Kits	92
Part Number Index	94

Page

Features

- Displacements of 4cc to 63cc
- Plain bearings for heavy duty applications
- Drive shafts SAE or ISO
- Multiple Pump Assemblies
- Port connections: flange or threaded
- Optimized pressure pulsation, which reduces noise levels and vibration excitation in the system
- Consistent high quality
- Considerably longer life due to reinforced shaft and housing




Fig. 1

- ① Gears
- ② Bearings
- ③ Extruded aluminium body
- ④ Covers
- ⑤ Shaft seal
- ⑥ Plain-bearing
- ⑦ Thrust pressure seal
- ⑧ Center coupling




Fig. 2

There is no doubt that the gear-type pump is the most widely used design in hydraulic systems. It is simple in construction, reliable in operation and the most cost-effective way of generating hydraulic pressure.

Bosch Rexroth has been involved with the design, development and manufacture of gear pumps for many decades. Well-proven designs, the use of specially developed materials, constant testing and sophisticated mass production techniques ensure products of the very highest quality. Universal application is assured by a carefully graded range of sizes and a variety of different design options.

Basic design

The pump (see FIG. 2) consists essentially of a pair of gears ① supported in bearings ② and the body ③ with front and rear covers ④ and ④1. The drive shaft protrudes from the front cover where it is sealed by the shaft seal ⑤.

The bearing forces are absorbed by special bearing-bushings with sufficient elasticity to produce surface contact instead of line contact ⑥. They also assure good operation under emergency conditions especially at low speed.

The gears have 12 teeth and this keeps both flow pulsation and noise emission to a minimum.

The internal sealing is pressure-sensitive, which provides optimum efficiency.

The bearings provide the seal at the ends of the gaps between the teeth, which carry the pressurized oil ②. The sealing zone between the gear teeth and the bearings is controlled by the admission of operating pressure to the rear of the bearings. Special seals ⑦ form the boundary of the zone.

The radial clearance at the tips of the gear teeth is sealed by forcing them against the body.

Specifications & Ratings

General	
Construction	external gear-type pump
Mounting	flange or through-bolting with pilot
Line connections	screw, flange
Direction of rotation (Fig. 4)	clockwise or counter-clockwise The pump may only be driven in the direction indicated.
Mounting position	any
Ambient temperature range	-15 °C to +60 °C (+5°F to 140°F)
Fluid	mineral oil-based hydraulic fluids to DIN/ISO, other fluids to order
Viscosity – centistokes (mm ² /s)	12 ... 800 mm ² /s permitted range 20 ... 100 mm ² /s recommended range ... 2000 mm ² /s max. cold start
Fluid temperature range	-15 °C to +80 °C (+5°F to 176°F)
Filter **) (further informations see page 27)	contamination class 10 to NAS 1638 obtained with filter $\beta_{25} = 75$

**) During the application of control systems or devices with critical counter-reaction, such as steering and brake valves, the type of filtration selected must be adapted to the sensitivity of these devices/systems.



Safety requirements pertaining to the whole system are to be observed.

In the case of applications with high numbers of load cycles please check.

As viewed looking at end of drive shaft.

Definitions of pressures

Note: Dimensional drawings always show clockwise-rotation pumps. On counter-clockwise-rotation pumps, the positions of the drive shaft and the suction and delivery ports are different.



Duration of load

p_1 max. continuous pressure
 p_2 max. intermittent pressure
 p_3 max. peak pressure



Fig. 4

Design calculations for pumps

The design calculations for pumps are based on the following parameters:

V [cm³/rev] Displacement
 Q [l/min] Delivery
 p [bar] Pressure
 M [Nm] Drive torque
 n [rev/min] Drive speed
 P [kW] Drive power

It is also necessary to allow for different efficiencies such as:

η_v Volumetric efficiency
 η_{hm} Hydraulic-mechanical efficiency
 η_t Overall efficiency

The formulas down in Fig. 5 describe the various relationships. They include correction factors for adapting the parameters to the usual units encountered in practice.




Diagram illustrating the relationships between pump parameters:

- Flow: Q
- Pressure: p
- Drive torque: M
- Drive speed: n

Conversion factors:

- $n \xrightarrow{[\%]} \eta_v \xrightarrow{\longrightarrow} Q$
- $M \xrightarrow{[\%]} \eta_{hm} \xrightarrow{\longrightarrow} p$
- $P \xrightarrow{[\%]} \eta_t \xrightarrow{\longrightarrow} p \cdot Q$

$Q = V \cdot n \cdot \eta_v \cdot 10^{-3}$	$V = \frac{Q}{n \cdot \eta_v} \cdot 10^3$	$n = \frac{Q}{V \cdot \eta_v} \cdot 10^3$
$p = \frac{M \cdot \eta_{hm}}{1,59 \cdot V}$	$V = \frac{M \cdot \eta_{hm}}{1,59 \cdot p}$	$M = 1,59 \cdot V \cdot p \frac{1}{\eta_{hm}}$
$\frac{p \cdot Q}{6 \cdot \eta_t} = \frac{600}{600}$	$Q = \frac{6 \cdot P \cdot \eta_t}{p}$	$p = \frac{6 \cdot P \cdot \eta_t}{Q}$
V [cm ³ /U]	Q [l/min]	p [bar]
n [U/min]	P [kW]	M [Nm]
Note Attention	η [%]	z. B. e.g. 95 [%] p.e.

Fig. 5

Notes on installation

Further information
see "General operating and Maintenance Instructions".
⊕ 1 987 762 101

Installation and commissioning

- Fill the pump with fluid before installing.
- Check the direction of rotation.
- Before installing the pump, clean the pipes thoroughly of all dirt, scale, sand, swarf, etc. Welded pipes in particular must be pickled or flushed out.
- Before starting up the pump for the first time, the entire hydraulic system must be thoroughly purged of air.
- Cover the shaft seal when spraying or brush-painting the equipment.
- Pay close attention to the specification, especially speeds, pressures and suction vacuum.

Filter recommendations

By far the largest number of premature failures to gear pumps are due to contaminated fluid.

Since our guarantee does not apply to wear resulting from dirt in the system, we recommend filtering, which reduces the size and concentration of the contamination particles to a permitted minimum.

Operating pressure [bar]	>160	<160
Contamination class NAS 1638	9	10
Contamination class ISO 4406	18/15	19/16
Achieved with filter $\beta_x = 75$	20	25

Fig. 6

Full-flow filtering is always recommended.

The initial contamination of the fluid with which the system is filled must not exceed Class 10 to NAS 1638. Past experience has shown that even brand new fluids often exceed this value. In such cases a filter incorporating a special element will have to be used.

Drive arrangements

1. Flexible couplings

The coupling must not transfer any radial or axial forces to the pump.

The maximum radial runout of shaft pilot is 0.2 mm. Refer to the fitting instructions provided by the coupling manufacturer for details of the maximum permitted shaft misalignment.





Fig. 7

2. Sleeve couplings

Used on shafts with DIN or SAE splining. **Note:** There must be no radial or axial forces exerted on the pump or sleeve coupling. The sleeve must be free to move axially. The distance between the pump shaft and drive shaft must be 2^{+1} . Oil-bath or oil-mist lubrication is necessary.



3. Tang Drive (Ref. Fig. 8 & 9)

For the close-coupling of pumps to engines, gearboxes, etc. the pump shaft has a special drive dog which combines with a center coupling ③ (included with the pumps). There is no shaft seal.

The recommended arrangements and dimensions for the drive end and sealing are as follows.

① Drive shaft

Case-hardening steel DIN 17 210

e.g. 20 Mn CrS 5

case-hardened 0.6 deep; HRc 60 ±3.

Surface for sealing ring

ground without rifling $R_t \leq 4\mu\text{m}$

② Radial shaft seal

Rubber-covered seal (see DIN 3760, Type AS or double-lipped ring).

Cut 15° chamfer or fit shaft seal with protective sleeve.

F Series

M_{\max} [Nm]	V [cm^3/rev]	p_{\max} [bar]
65	16	230
	19	190
	22,5	160





Fig. 8

N Series



G Series




Fig. 9

4. V-belts and gearwheels without outrigger bearings

(Ref. Fig. 10)

When proposing to use V-belt or gearwheel drive, please submit details of the application for our comments (especially dimensions a , d_m , d_w and angle α).





Fig. 10

5. Outrigger bearings (Ref. Fig. 11)

Outrigger bearings eliminate possible problems when the pumps are driven by V-belts or gearwheels. The diagrams below show the maximum overhung and thrust loads that can be tolerated referred to a bearing life of $L_H = 1000$ hours.



Multiple gear pumps

F & N Series

Ref. Fig. 12

Gear pumps are well-suited to tandem combinations of pumps in which the drive shaft of the first pump is extended to drive a second pump, and sometimes a third pump in the same manner.

A coupling is fitted between each pair of pumps. In most cases, each pump is isolated from its neighbour, (i. e. the suction and delivery ports are separate).


Specifications: Basically, the specifications for the individual pumps apply, but with certain restrictions:

Max. speed: This is determined by the highest rated pump speed in use.

Pressures: These are restricted by the strength of the drive shaft, the transmissions and the couplings. Appropriate data is given in the dimensional drawings and the graph on the following page.

Multiple Gear Pumps

Combinations



M_{\max} (Torque)

F	65	F
N	65	F
N	95	N




Fig. 12

Multiple pump units – Pressure & Torque Ratings


In the case of Size F the center coupling for the second pump can carry a load of up to $M_{max} = 65 \text{ Nm}$. The pressure restriction for the second pump is as follows:

V [cm ³ /rev]	P _{max} [bar]
16	230
19	190
22.5	160

If the first pump is driven through a dog and center coupling or Type 1 outrigger bearing, the pressure restrictions for both pumps are as indicated in the diagram below.


In the case of applications with high numbers of load cycles, please contact the factory.

M_{max} = 65 [Nm]



Reinforced transmissions are available for applications with higher transfer torques and/or torsional vibrations.

Customized designs are available on request.



Beispiel, Example, Exemple

Fig. 13

Gear pumps with integral valves



In order to reduce external pipework it is possible to incorporate a flow control valve or pressure relief valve in the end cover of the pump. A typical application of this is in power-assisted steering systems. The pump delivers a constant flow irrespective of the speed at which it is driven. The excess flow is either returned internally to the suction or distributed externally to other items of equipment.





Fig. 14

Ordering Code (F Series Pump)

AZ	P	F - 1□ or 2□ - 016	R	R	R	12 M	B - □□□ □□ - S□□□□	Special Design*
Function								PRV(bar) FCV(l/min)
P = Pump								
Size (F)								
.26in ³ (4.1 cm ³) = 004								
.35in ³ (5.6 cm ³) = 005								
.51in ³ (8.2 cm ³) = 008								
.71in ³ (11.3 cm ³) = 011								
.89in ³ (14.3 cm ³) = 014								
1.03in ³ (16.5 cm ³) = 016								
1.22in ³ (19.5 cm ³) = 019								
1.43in ³ (22.9 cm ³) = 022								
1.59in ³ (25.4 cm ³) = 025								
1.78in ³ (28.5 cm ³) = 028								
Direction of rotation								
Right = R								
Left = L								
Drive shafts								
Matching front flange				Front flange			Line connections	
C	Conical 1:5 (Tapered key)		B P	B	Square flange Pilot Ø 80 mm		20	Rectangular flange
S	Conical 1:5 for flange A (Tapered key)		A	R	SAE A 2-bolt		12	Thread (UN-2B) SAE O-ring BOSS
H	Conical 1:8 (Tapered key)		O	P	Transmission flange Pilot Ø 50 mm		01	BSP Pipe thread ISO 228
N	Dog (Tang)		M	O	Square flange Pilot Ø 36.47 mm		30	Rectangular flange
A	Cylindrical (Straight key) ISO Ø 18mm		B	C	SAE B 2-bolt		07	Split flange SAE Code 61 Metric bolts
Q	Cylindrical (Straight key) SAE A 5/8"		R	M	Transmission flange Pilot Ø 52 mm with O-ring		40	Split flange SAE Code 61 UNC bolts
Q	SAE 3/4" Keyed, Long *Use S0022 suffix		R	A	Outrigger bearing Pilot Ø 80 mm (outboard bearing)			
R	Spline shaft SAE A 9T		R C					
P	Spline shaft SAE 11T		R C					
F	Spline shaft DIN 5482 B17x14		B P					

* Common SO Codes:
 S0022 – Long keyed shaft
 Contact Factory for additional codes.


**F Series Pump Product Index**


(Reference page 14 for ordering code designators)

AZPF-XX-XXXX**MB**


Page Number	Ordering code	Shaft Type	Flange	Mounting Ports	Port Orientation
23	AZPF-XX-XXXXRR12MB	R	R	12	side
24	AZPF-XX-XXXXRR12MA	R	R	12	rear
25	AZPF-XX-XXXXQR12MB	Q	R	12	side
26	AZPF-XX-XXXXQR12MA	Q	R	12	rear
27	AZPF-XX-XXXXPR12MB	P	R	12	side
28	AZPF-XX-XXXXQR12MB-S0022	Q-long	R	12	side
29	AZPF-XX-XXXXQR12MA-S0022	Q-long	R	12	rear
30	AZPF-XX-XXXXPC12MB	P	C	12	side
31	AZPF-XX-XXXXRR20MB	R	R	20	side
32	AZPF-XX-XXXXCB20MB	C	B	20	side
33	AZPF-XX-XXXXFB20MB	F	B	20	side
34	AZPF-XX-XXXXHO30MB	H	O	30	side
35	AZPF-XX-XXXXFO30MB	F	O	30	side
36	AZPF-XX-XXXXHO01MB	H	O	01	side
37	AZPF-XX-XXXXCN20MB	C	N	20	side
38	AZPF-XX-XXXXFN20MB	F	N	20	side
39	AZPF-XX-XXXXCP20MB-S0007	C	P	20	side
40	AZPF-XX-XXXXFP20PB	F	P	20	side
41	AZPF-XX-XXXXNT20MB	N	T	20	side
42	AZPF-XX-XXXXSA20MB	S	A	20	side
43	AZPF-XX-XXXXSG20MB	S	G	20	side

F Series Drive Shafts



F Series Front Cover


F Series Port Connections



01 Pipe thread
ISO 228/1

when pressure $p_2 > 210$ bar
limited fatigue strength


Synopsis of Types	Size	Pressure port			Suction port		
		G	F		G	F	
01	4 ... 16 cm ³	G 1/2	16		G 3/4	16	
	19 ... 28 cm ³	G 3/4			G1	19	



03 Thread metric
ISO 6149
with O-ring

when pressure $p_2 > 210$ bar
limited fatigue strength


Synopsis of Types	Size	Pressure port				Suction port			
		M	D	E	F	M	D	E	F
03	4 ... 5.5 cm ³	M 18 x 1.5	29	0.5	14.5	M 18 x 1.5	29	0.5	14.5
	8 ... 16 cm ³	M 22 x 1.5	34		18	M 27 x 1.5	40		19
	19 ... 28 cm ³					M 33 x 1.5	46		22



12 Thread
(UN-2B) SAE
O-ring BOSS


when pressure $p_2 > 210$ bar
limited fatigue strength

Synopsis of Types	Size	Pressure port				Suction port			
		G	D	E	F	G	D	E	F
12	4 ... 5.5 cm ³	SAE - 8	25	0.5	13	SAE - 10	25	0.5	13
	8 ... 14 cm ³	SAE - 10	35		16	SAE - 12	35		16
	16 ... 28 cm ³	SAE - 10				SAE - 16	45		19



20 Rectangular flange
DIN 8901/8902

Synopsis of Type	Size	Pressure port			Suction port		
		C	D	E	C	D	E
20	4 ... 5.5 cm ³	15	35	M 6 depth 13	15	40	M 6 depth 13
	8 ... 16 cm ³				20		
	19 ... 28 cm ³				26	55	M 8 depth 13



30 Rectangular flange

Synopsis of Type	Size	Pressure port			Suction port		
		C	D	E	C	D	E
30	4 ... 8 cm ³	13.5	30.2	M 6 depth 13	13.5	30.2	M 6 depth 13
	11 ... 28 cm ³				20.0	39.7	M 8 depth 13

F Series Performance Ratings

Size		004	005	008	011	014	016	019	022	025	028
Displacement	cm³/rev	4.1	5.6	8.2	11.3	14.3	16.5	19.5	22.9	25.4	28.5
Inlet pressure	bar							min. 0.7 max. 3 (absolute)			
max. continuous pressure p ₁	bar			250				210	180	200	170
	psi			3625				3045	2610	2900	2465
max. intermittent pressure p ₂	bar			280				230	210	220	190
	psi			4060				3335	3045	3190	2755
max. peak pressure p ₃	bar			300				250	230	240	210
	psi			4350				3625	3335	3528	3045
min. rotational speed (RPM) ≤ 100	RPM	600	500	500	500	500	500	500	500	500	500
max. rotational speed at (RPM)	p ₁		3500		3000	2500	2000	2000	2000	2000	2000
	p ₂		4000		3500	3500	3500	3000	2750	2500	2500

F Series Pumps**SAE O-Ring BOSS - Standard Porting**


Displacement (cc)	Side Ports			Rear Port		
	Inlet	Outlet	Inlet	Outlet	Outlet	Outlet
4	-10	-8	-12	-12	-10	-10
5	-10	-8	-12	-12	-10	-10
8	-12	-10	-12	-12	-10	-10
11	-12	-10	-12	-12	-10	-10
14	-12	-10	-12	-12	-10	-10
16	-16	-10	-12	-12	-10	-10
19	-16	-10	-12	-12	-10	-10
22	-16	-10	-12	-12	-10	-10
25	-16	-10	-12	-12	-10	-10
28	-16	-10	-12	-12	-10	-10

SAE Porting - Specifications and Dimensions

per SAE J1926/1

Dash Size	Thread Size (in)
-2	5/16-24 UNF-2B
-3	3/8-24 UNF-2B
-4	7/16-20 UNF-2B
-5	1/2-20 UNF-2B
-6	9/16-18 UNF-2B
-8	3/4-16 UNF-2B
-10	7/8-14 UNF-2B
-12	1-1/16-12 UN-2B
-14	1-3/16-12 UN-2B
-16	1-5/16-12 UN-2B
-20	1-5/8-12 UN-2B
-24	1-7/8-12 UN-2B
-32	2-1/2-12 UN-2B

Note: Ratings represent units incorporating SAE O-Ring BOSS threaded ports. Pressure ratings may differ for other types of ports.



Unit Conversions


Pressure: psi = bar x 14.7





Torque: ft-lbs = (Nm) x .738





Power: hp = (kW) x 1.341


Volume: in³ = (cc) x 16.39

gpm = (LPM) x .2642



8 cm³/rev**11 cm³/rev****14 cm³/rev****16 cm³/rev**

19 cm³/rev**22.5 cm³/rev****25 cm³/rev****28 cm³/rev**



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPF - X X - □ □ □ □ R R 12 MB


Displacement [cm ³ /rev]		Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]					
						A	B	C	Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)	
4.0		9 510 290 036		9 510 290 015	250	4000	85.0	39.9	39.9	-10	-8
5.5		9 510 290 037		9 510 290 005	250	4000	85.6	41.1	41.1	-10	-8
8.0		9 510 290 038		9 510 290 017	250	4000	91.6	43.2	43.2	-12	-10
11.0		9 510 290 039		9 510 290 018	250	3500	96.6	47.0	47.0	-12	-10
14.0		9 510 290 040		9 510 290 004	250	3000	101.8	47.5	47.5	-12	-10
16.0		9 510 290 127		9 510 290 056	250	3000	105.0	47.5	47.5	-16	-10
19.0		9 510 290 128		9 510 290 125	210	3000	110.0	47.5	47.5	-16	-10
22.5		9 510 290 129		9 510 290 126	180	2500	115.4	55.1	55.1	-16	-10
25.0		9 510 290 117		9 510 290 111	200	3000	131.6	63.2	63.2	-16	-10
28.0		9 510 290 120		9 510 290 114	170	3000	136.4	65.6	65.6	-16	-10

* Contact factory for availability of units with no ordering number listed.

** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	9t spline
Front Cover	SAE A 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPF - 12 - □ □ □ □ R R 12 MA

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B	C		
4.0	9 510 290 083	9 510 290 075	250	4000	100.3	85.0		-12	-10
5.5	9 510 290 084	9 510 290 076	250	4000	103.3	88.4		-12	-10
8.0	9 510 290 085	9 510 290 077	250	4000	107.4	92.5		-12	-10
11.0	9 510 290 086	9 510 290 078	250	3500	112.4	97.5		-12	-10
14.0	9 510 290 087	9 510 290 079	250	3000	117.4	102.5		-12	-10
16.0	9 510 290 088	9 510 290 080	250	3000	120.8	105.9		-12	-10
19.0	9 510 290 089	9 510 290 081	210	3000	126.8	110.9		-12	-10
22.5	9 510 290 090	9 510 290 082	180	2500	131.2	116.3		-12	-10
25.0	*	*							
28.0	*	*							

* Contact factory for availability of units with no ordering number listed.


** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code****AZPF - 1 2 - □ □ □ □ Q R 12 MB**


Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
					[mm]	A	B	C		
4.0	9 510 290 044	9 510 290 021	250	4000	85.0	39.9	39.9	-10	-8	
5.5	9 510 290 045	9 510 290 022	250	4000	85.6	41.1	41.1	-10	-8	
8.0	9 510 290 046	9 510 290 023	250	4000	91.6	43.2	43.2	-12	-10	
11.0	9 510 290 047	9 510 290 024	250	3500	96.6	47.0	47.0	-12	-10	
14.0	9 510 290 048	9 510 290 025	250	3000	101.6	47.5	47.5	-12	-10	
16.0	9 510 290 130	9 510 290 122	250	3000	105.0	47.5	47.5	-16	-10	
19.0	9 510 290 131	9 510 290 123	210	3000	110.0	47.5	47.5	-16	-10	
22.5	9 510 290 132	9 510 290 124	180	2500	115.4	55.1	55.1	-16	-10	
25.0	9 510 290 118	9 510 290 112	200	3000	131.6	63.2	63.2	-16	-10	
28.0	9 510 290 121	9 510 290 115	170	3000	136.4	65.6	65.6	-16	-10	

* Contact factory for availability of units with no ordering number listed.

** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	5/8" keyed
Front Cover	SAE A 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPF - 1 2 - □ □ □ □ Q R 12 MA

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B	C		
4.0	9 510 290 099	9 510 290 091	250	4000	100.8	85.9		-12	-10
5.5	9 510 290 100	9 510 290 092	250	4000	103.3	88.4		-12	-10
8.0	9 510 290 101	9 510 290 093	250	4000	107.4	92.5		-12	-10
11.0	9 510 290 102	9 510 290 094	250	3500	112.4	97.5		-12	-10
14.0	9 510 290 103	9 510 290 095	250	3000	117.4	102.5		-12	-10
16.0	9 510 290 104	9 510 290 096	250	3000	120.8	105.9		-12	-10
19.0	9 510 290 105	9 510 290 097	210	3000	126.8	110.9		-12	-10
22.5	9 510 290 106	9 510 290 098	180	2500	131.2	116.3		-12	-10
25.0	*	*							
28.0	*	*							

* Contact factory for availability of units with no ordering number listed.


** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.




Displacement [cm³/rev]	Ordering-Number *	Ordering-Number *	Max. operating pressure [bar]	Max. rotation speed [min⁻¹]	Dimension [mm]				
					A	B	C	Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
4.0	9 510 290 065	9 510 290 057	250	4000	85.0	40.5	40.5	-10	-8
5.5	9 510 290 066	9 510 290 058	250	4000	85.6	41.1	41.1	-10	-8
8.0	9 510 290 067	9 510 290 059	250	4000	91.6	43.2	43.2	-12	-10
11.0	9 510 290 068	9 510 290 060	250	3500	96.6	47.0	47.0	-12	-10
14.0	9 510 290 069	9 510 290 061	250	3000	101.6	47.5	47.5	-12	-10
16.0	9 510 290 070	9 510 290 062	250	3000	105.0	49.9	49.9	-16	-10
19.0	9 510 290 071	9 510 290 063	210	3000	110.0	52.4	52.4	-16	-10
22.5	9 510 290 072	9 510 290 064	180	2500	115.4	55.1	55.1	-16	-10
25.0	9 510 290 116	9 510 290 110	200	3000	131.6	63.2	63.2	-16	-10
28.0	9 510 290 119	9 510 290 113	170	3000	136.4	65.6	65.6	-16	-10

* Contact factory for availability of units with no ordering number listed.

** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	5/8" keyed - long
Front Cover	SAE A 2-bolt
Ports	SAE ORB
Rear Cover	Standard



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPF - 1 2 - □ □ □ □ Q R 12 MB - S0022

Displacement [cm³/rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min⁻¹]	Dimension [mm]			Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B	C		
4.0	*	*							
5.5	*	9 510 290 259	250	4000	85.6	41.1	41.1	-10	-8
8.0	9 510 290 214	9 510 290 191	250	4000	91.6	43.2	43.2	-12	-10
11.0	9 510 290 254	9 510 290 209	250	3500	96.6	47.0	47.0	-12	-10
14.0	9 510 290 215	9 510 290 133	250	3000	101.6	47.5	47.5	-12	-10
16.0	9 510 290 255	9 510 290 210	250	3000	105.0	49.9	49.9	-16	-10
19.0	9 510 290 256	9 510 290 211	210	3000	110.0	52.4	52.4	-16	-10
22.5	9 510 290 257	9 510 290 212	180	2500	115.4	55.1	55.1	-16	-10
25.0	*	*							
28.0	*	*							

* Contact factory for availability of units with no ordering number listed.



** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code****AZPF - 1 2 - □□□ Q R 12 MA - S0022**

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B	C		
4.0	*	*							
5.5	*	*							
8.0	*	*							
11.0	*	9 510 290 134	250	3500	112.4	97.5		-12	-10
14.0	*	*							
16.0	*	*							
19.0	9 510 290 135	9 510 290 213	210	3000	125.8	110.9		-12	-10
22.5	*	*							
25.0	*	*							
28.0	*	*							

* Contact factory for availability of units with no ordering number listed.

** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	11t spline
Front Cover	SAE B 2-bolt
Ports	SAE ORB
Rear Cover	Standard


Ordering code

AZPF - 1 2 - □ □ □ □ PC 12 MB

Displacement [cm³/rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min⁻¹]	Dimension [mm]			Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
					A	B	C		
4.0	*	9 510 290 323	250	4000	85.0	40.5	40.5	-10	-8
5.5	*	9 510 290 324	250	4000	85.0	41.1	41.1	-10	-10
8.0	*	9 510 290 325	250	4000	91.6	43.2	43.2	-12	-10
11.0	*	9 510 290 326	250	3500	96.6	47.0	47.0	-12	-10
14.0	*	9 510 290 327	250	3000	101.6	47.5	47.5	-12	-10
16.0	*	9 510 290 328	250	3000	105.0	49.9	49.9	-16	-10
19.0	*	9 510 290 329	210	3000	110.0	52.4	52.4	-16	-10
22.5	*	9 510 290 330	180	2500	115.4	55.1	55.1	-16	-10
25.0	*	9 510 290 331	200	3000	131.6	63.2	63.2	-16	-10
28.0	*	9 510 290 332	170	3000	136.4	65.6	65.6	-16	-10

* Contact factory for availability of units with no ordering number listed.


** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code**

AZPF - 1 2 - □□□ R R 20 MB

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			
					A	B	C	D
4.0	0 510 225 314	0 510 225 013	250	4000	39.9	85.0		
5.5	0 510 325 313	0 510 325 013	250	4000	41.1	87.5		
8.0	0 510 425 314	0 510 425 020	250	4000	43.2	91.6		
11.0	0 510 525 324	0 510 525 019	250	3500	47.0	96.6		
14.0	0 510 525 325	0 510 525 020	250	3000	47.5	101.6		
16.0	0 510 625 329	0 510 625 028	250	3000	47.5	105.0		
19.0	0 510 625 330	0 510 625 029	210	3000	47.5	110.0		
22.5	0 510 725 361	0 510 725 077	180	2500	55.1	115.4		
25.0								
28.0								


* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPF - X X - □ □ □ □ C B 20 MB

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			
	L	R			A	B		
4.0	0 510 225 306	0 510 225 006	250	4000	39.8	85.2		
5.5	0 510 325 306	0 510 325 006	250	4000	41.1	87.5		
8.0	0 510 425 307	0 510 425 009	250	4000	43.1	91.8		
11.0	0 510 525 311	0 510 525 009	250	3500	47.5	96.8		
14.0	0 510 525 319	0 510 525 018	250	3000	47.5	101.8		
16.0	0 510 625 315	0 510 625 022	250	3000	47.5	105.2		
19.0	0 510 625 314	0 510 625 013	210	3000	47.5	110.2		
22.5	0 510 725 330	0 510 725 030	180	2500	55.0	115.6		
25.0								
28.0								


* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPF - X X - □ □ □ □ FB 20 MB

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]	
	L	R			A	B
4.0	0 510 225 307	0 510 225 007	250	4000	39.8	85.2
5.5	0 510 325 307	0 510 325 007	250	4000	41.0	87.5
8.0	0 510 425 308	0 510 425 010	250	4000	43.1	91.8
11.0	0 510 525 312	0 510 525 010	250	3500	47.5	96.6
14.0	0 510 525 328	0 510 525 030	250	3000	47.5	101.8
16.0	0 510 625 317	0 510 625 015	250	3000	47.5	105.2
19.0	0 510 625 316	0 510 625 014	210	3000	47.5	110.2
22.5		0 510 725 062	180	2500	55.0	115.6
25.0						
28.0						


* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPF - X X - □ □ □ □ H O 30 MB

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
	L	R			A	B	C	D	E
4.0	0 510 225 308	0 510 225 008	280	4000	41.4	86.5	30.2	13.5	M6
5.5	0 510 325 308	0 510 325 008	280	4000	42.5	89.0	30.2	13.5	M6
8.0	0 510 425 309	0 510 425 011	280	4000	44.6	93.3	30.2	13.5	M6
11.0	0 510 525 313	0 510 525 011	280	3500	49.0	98.3	39.7	20.0	M8
14.0	0 510 525 314	0 510 525 012	280	3000	49.0	103.1	39.7	20.0	M8
16.0	0 510 625 318	0 510 625 016	280	3000	49.0	106.5	39.7	20.0	M8
19.0	0 510 625 319	0 510 625 017	210	3000	49.0	111.5	39.7	20.0	M8
22.5	0 510 725 331	0 510 725 031	180	2500	56.6	116.9	39.7	20.0	M8
25.0									
28.0									


* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPF - X X - □ □ □ □ F O 30 MB

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
	L	R			A	B	C	D	E
8.0	0 510 425 315	0 510 425 021	250	4000	44.6	93.3	30.2	13.5	M6
11.0	0 510 525 323	0 510 525 024	250	3500	48.5	98.1	39.7	20.0	M8


* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPF - X X - □ □ □ □ H O 01 MB


Displacement [cm ³ /rev]	L	Ordering-Number *	R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			
						A	B		
4.0		0 510 225 015		250	4000	41.4	86.5		
5.5		0 510 325 018		250	4000	42.6	89.0		
8.0		0 510 425 027		250	4000	44.7	93.1		
11.0		0 510 525 039		250	3500	48.5	98.1		
14.0		0 510 525 040		250	3000	49.0	103.1		
16.0		0 510 625 047		250	3000	49.0	106.5		
19.0		0 510 625 052		210	3000	49.0	111.5		
22.5		0 510 725 084		180	2500	56.6	116.4		
25.0									
28.0									

* Contact factory for availability of units with no ordering number listed.

**Ordering code****AZPF - X X - □ □ □ □ C N 20 MB**

Displacement [cm³/rev]			Max. operating pressure [bar]	Max. rotation speed [min⁻¹]	Dimension [mm]		
					A	B	C
4.0	0 510 215 306	0 510 215 006	250	4000	37.4	73.7	
5.5	0 510 315 304	0 510 315 004	250	4000	38.6	76.2	
8.0	0 510 415 313	0 510 415 005	250	4000	40.7	80.3	
11.0	0 510 515 310	0 510 515 004	250	3500	44.5	85.3	
14.0		0 510 515 015	250	3000	45.0	90.3	
16.0	0 510 615 314	0 510 615 006	250	3000	45.0	93.7	
19.0	0 510 615 341		210	3000	45.0	98.7	
22.5		0 510 715 016	180	2500	58.6	116.1	
25.0							
28.0							


* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPF - X X - □ □ □ □ FN 20 MB

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]					
	L	R			A	B				
5.5		0 510 315 007	250	4000	38.6	76.2				
11.0		0 510 515 011	250	3500	45.0	85.3				
19.0		0 510 615 009	210	3000	45.0	98.7				


* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPF - X X - □ □ □ □ C P 20 MB - S0007

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			
					A	B	C	D
4.0	0 510 215 309	0 510 215 009	250	4000	37.3	73.7		
5.5	0 510 315 307	0 510 315 006	250	4000	38.6	76.2		
8.0	0 510 415 316		250	4000	40.6	80.3		
11.0	0 510 515 309	0 510 515 007	250	3500	45.0	85.3		
14.0	0 510 515 316	0 510 515 018	250	3000	45.0	90.3		
16.0	0 510 615 317	0 510 615 010	250	3000	45.0	93.7		
19.0	0 510 615 318	0 510 615 005	210	3000	45.0	98.7		
22.5	0 510 715 306		180	2500	52.5	104.1		
25.0								
28.0								


* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPF - X X - □ □ □ □ F P 20 PB


Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			
	L	R			A	B	C	D
8.0	0 510 415 328		250	4000	40.7	80.3		
11.0	0 510 515 337	0 510 515 012	250	3500	44.5	85.3		
14.0	0 510 515 338	0 510 515 013	250	3000	45.0	90.3		
16.0		0 510 615 023	250	3000	45.0	93.7		
22.5	0 510 715 320	0 510 715 008	180	2500	58.6	116.1		

* Contact factory for availability of units with no ordering number listed.

**Ordering code****AZPF - X X - □ □ □ □ N T 20 MB**


Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			
					A	B	C	D
4.0	0 510 215 307	0 510 215 007	250	4000	37.4	73.7		
5.5	0 510 315 305	0 510 315 005	250	4000	38.6	76.2		
8.0	0 510 415 314	0 510 415 006	250	4000	40.7	80.3		
11.0	0 510 515 311	0 510 515 005	250	3500	44.5	85.3		
14.0	0 510 515 340	0 510 515 019	250	3000	45.0	90.3		
16.0	0 510 615 315	0 510 615 007	250	3000	45.0	93.7		
19.0	0 510 615 321	0 510 615 008	210	3000	45.0	98.7		
22.5	0 510 715 307	0 510 715 004	180	2500	52.6	104.1		
25.0								
28.0								

* Contact factory for availability of units with no ordering number listed.

**Ordering code****AZPF - X X - □ □ □ □ S A 20 MB**

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			
	L	R			A		B	
4.0	0 510 245 300	0 510 245 001	250	4000	71.3	116.7		
5.5	0 510 345 300	0 510 345 001	250	4000	72.6	119.2		
8.0	0 510 445 300	0 510 445 001	250	4000	74.7	121.5		
11.0	0 510 545 300	0 510 545 001	250	3500	79.0	126.5		
16.0	0 510 645 300	0 510 645 004	250	3000	79.0	134.9		
19.0		0 510 645 002	210	3000	79.0	134.9		

* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPF - X X - □ □ □ S G 20 MB

Displacement [cm ³ /rev]		Ordering-Number *	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]	
					A	B
11.0		0 510 545 003	250	3500	64.5	113.8
14.0	0 510 545 302	0 510 545 002	250	3000	65.0	119.1
16.0		0 510 645 005	250	3000	65.0	122.5
19.0		0 510 645 003	210	3000	65.0	127.5

* Contact factory for availability of units with no ordering number listed.


Ordering Code (N Series Pump)

A	Z	P	N	-	1	□	-	0	3	2	R	D	C	1	2	M	B	-	S	□	□	□	□	*	
Function																			End cover						
P = Pump																			Standard = B						
Size (N)																			Rear Ports = A						
1.28 in³ (20.4 cm³) = 020																									
1.44 in³ (23.1 cm³) = 022																									
1.61 in³ (25.8 cm³) = 025																									
1.78 in³ (28.4 cm³) = 028																									
2.02 in³ (32.4 cm³) = 032																			Seals						
2.28 in³ (36.4 cm³) = 036																			NBR = M						
																			FPM = P						
																			NBR, shaft seal in FPM = K						
Direction of rotation																									
Right = R																									
Left = L																									
Drive shafts																			Front flange						
C Conical 1:5 (Tapered key)																			B Matching front flange						
N Dog (Tang)																			B Square flange Pilot Ø 100 mm						
D Spline shaft SAE B 13T																			C SAE B 2-bolt						
P Spline shaft SAE 11T																			M Transmission flange Pilot Ø 52 mm with O-ring						
Q SAE 3/4" Keyed Short																			R SAE A 2-bolt						
Q SAE 3/4" Keyed Long - use S0022 Suffix																									
X Special (SO Code Defines Special Shaft)																									
Front flange																			Line connections						
B																			20	Rectangular flange					
C																			12	Thread (UN-2B) SAE O-ring BOSS					
M																			07	Split flange SAE Code 61 Metric bolts					
R																			40	Split flange SAE Code 61 UNC bolts					

* Common Suffix Codes:

S0075 – Tapered shaft

Contact Factory for additional codes.

**N Series Pump Product Index**

(Reference page 43 for ordering code designators)

AZPF-XX-XXXX - - - **MB**

Page Number	Ordering code	Shaft Type	Mounting Flange	Ports	Port Orientation
49	AZPN-12-XXXXPC12MB	P	C	12	side
50	AZPN-12-XXXXPC12MA	P	C	12	rear
51	AZPN-12-XXXXPR12MB	P	R	12	side
52	AZPN-12-XXXXPR12MA	P	R	12	rear
53	AZPN-12-XXXXQC12MB	Q	C	12	side
54	AZPN-12-XXXXQC12MA	Q	C	12	rear
55	AZPN-12-XXXXQR12MB	Q	R	12	side
56	AZPN-12-XXXXQR12MA	Q	R	12	rear
57	AZPN-12-XXXXRR12MB	R	R	12	side
58	AZPN-12-XXXXRR12MA	R	R	12	rear
59	AZPN-12-XXXXDC12MB	D	C	12	side
60	AZPN-12-XXXXDC12MA	D	C	12	rear
61	AZPN-12-XXXXDR12MB	D	R	12	side
62	AZPN-12-XXXXDR12MA	D	R	12	rear
63	AZPN-12-XXXXXR12MB-S0075	X-S0075	R	12	side
64	AZPN-12-XXXXXR12MA-S0075	X-S0075	R	12	rear
65	AZPN-12-XXXXDC20MB	D	C	20	side
66	AZPN-12-XXXXCB20MB	C	B	20	side
67	AZPN-12-XXXXNM20MB	N	M	20	side

N Series Performance Ratings

Size		020	022	025	028	032	036
Displacement	cm ³ /rev	20.4	23.1	25.8	28.4	32.4	36.4
Inlet pressure	bar			min. 0.7 max. 3 (absolute)			
max. continuous pressure p ₁	bar	230	230	230	210	180	160
	psi	3335	3335	3335	3045	2610	2610
max. intermittent pressure p ₂	bar	250	250	250	230	200	180
	psi	3625	3625	3625	3335	2900	2610
max. peak pressure p ₃	bar	270	270	270	250	220	200
	psi	3915	3915	3915	3625	3190	2900
min. rotational speed (RPM) ≤ 100	RPM	500	500	500	500	500	500
max. rotational speed at (RPM) p ₁		2500	2500	2500	2300	2300	2100
p ₂		3000	3000	3000	2800	2800	2600

N Series Pumps**SAE O-Ring BOSS - Standard Porting**

Displacement (cc)	Side Ports		Rear Port	
	Inlet	Outlet	Inlet	Outlet
20	-16	-10	-16	-12
22	-16	-10	-16	-12
25	-20	-12	-16	-12
28	-20	-12	-16	-12
32	-20	-12	-16	-12
36	-20	-12	-16	-12

SAE Porting - Specifications and Dimensions

per SAE J1926/1

Dash Size	Thread Size (in)
-2	5/16-24 UNF-2B
-3	3/8-24 UNF-2B
-4	7/16-20 UNF-2B
-5	1/2-20 UNF-2B
-6	9/16-18 UNF-2B
-8	3/4-16 UNF-2B
-10	7/8-14 UNF-2B
-12	1-1/16-12 UN-2B
-14	1-3/16-12 UN-2B
-16	1-5/16-12 UN-2B
-20	1-5/8-12 UN-2B
-24	1-7/8-12 UN-2B
-32	2-1/2-12 UN-2B

Note: Ratings represent units incorporating SAE O-Ring BOSS threaded ports. Pressure ratings may differ for other types of ports.


Diagrams

Size **N**


$v = 35 \text{ mm}^2/\text{s}$, $T = 50^\circ\text{C}$

Unit Conversions


Pressure: psi = bar x 14.7
 Torque: ft-lbs = (Nm) x .738
 Power: hp = (kW) x 1.341
 Volume: in³ = (cc) x 16.39
 gpm = (LPM) x .2642








20 cm³/rev



22.5 cm³/rev




25 cm³/rev**28 cm³/rev****32 cm³/rev****36 cm³/rev**

**Ordering code****AZPN - X X - □ □ □ □ P C 12 MB**


Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
	L	R			A	B	C	Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
20.0	9 510 390 153	9 510 390 147	230	3000	109.8	52.1	52.1	-16	-10
22.0	9 510 390 154	9 510 390 148	230	3000	114.7	53.6	53.1	-16	-10
25.0	9 510 390 155	9 510 390 149	230	3000	115.8	55.1	55.1	-20	-12
28.0	9 510 390 156	9 510 390 150	210	2800	118.8	56.6	56.1	-20	-12
32.0	9 510 390 157	9 510 390 151	180	2800	123.3	58.8	58.8	-20	-12
36.0	9 510 390 158	9 510 390 152	160	2600	129.7	61.1	61.1	-20	-12

* Contact factory for availability of units with no ordering number listed.

** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	11t spline
Front Cover	SAE B 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPN - X X - □ □ □ □ P C 12 MA

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B		
20.0	9 510 390 104	9 510 390 098	230	3000	128.1	110.0	-16	-12
22.0	9 510 390 105	9 510 390 099	230	3000	131.1	114.9	-16	-12
25.0	9 510 390 106	9 510 390 100	230	3000	134.1	116.0	-16	-12
28.0	9 510 390 107	9 510 390 101	210	2800	137.1	119.0	-16	-12
32.0	9 510 390 108	9 510 390 102	180	2800	141.6	123.5	-16	-12
36.0	9 510 390 109	9 510 390 103	160	2600	146.1	124.4	-16	-12

* Contact factory for availability of units with no ordering number listed.


** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code****AZPN - X X - □ □ □ □ P R 12 MB**


Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
	L	R			A	B	C	Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
20.0	9 510 390 165	9 510 390 159	230	3000	115.4	58.1	58.1	-16	-10
22.0	9 510 390 166	9 510 390 160	230	3000	118.4	59.6	59.6	-16	-10
25.0	9 510 390 167	9 510 390 161	230	3000	121.4	61.1	61.1	-20	-12
28.0	9 510 390 168	9 510 390 162	210	2800	124.4	62.6	62.6	-20	-12
32.0	9 510 390 169	9 510 390 163	180	2800	128.5	64.8	64.8	-20	-12
36.0	9 510 390 170	9 510 390 164	160	2600	133.0	67.1	67.1	-20	-12

* Contact factory for availability of units with no ordering number listed.

** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	11t spline
Front Cover	SAE A 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPN - X X - □ □ □ □ P R 12 MA

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B		
20.0	9 510 390 092	9 510 390 086	230	3000	134.1	116.0	-16	-12
22.0	9 510 390 093	9 510 390 087	230	3000	137.1	120.9	-16	-12
25.0	9 510 390 094	9 510 390 088	230	3000	140.1	122.0	-16	-12
28.0	9 510 390 095	9 510 390 089	210	2800	143.1	125.0	-16	-12
32.0	9 510 390 096	9 510 390 090	180	2800	147.6	129.5	-16	-12
36.0	9 510 390 097	9 510 390 091	160	2600	152.1	135.9	-16	-12

* Contact factory for availability of units with no ordering number listed.


** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code****AZPN - X X - □ □ □ □ Q C 12 MB**

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
					A	B	C	Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
20.0	9 510 390 055	9 510 390 049	230	3000	109.4	52.1	52.1	-16	-10
22.0	9 510 390 056	9 510 390 050	230	3000	112.4	53.6	53.6	-16	-10
25.0	9 510 390 057	9 510 390 051	230	3000	115.4	55.1	55.1	-20	-12
28.0	9 510 390 058	9 510 390 052	210	2800	118.4	56.6	56.6	-20	-12
32.0	9 510 390 059	9 510 390 053	180	2800	122.5	58.8	58.8	-20	-12
36.0	9 510 390 060	9 510 390 054	160	2600	127.0	61.1	61.1	-20	-12

* Contact factory for availability of units with no ordering number listed.

** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.


**Ordering code**

AZPN - X X - □ □ □ □ Q C 12 MA

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B		
20.0	9 510 390 067	9 510 390 061	230	3000	128.1	110.0	-16	-12
22.0	9 510 390 068	9 510 390 062	230	3000	131.1	114.9	-16	-12
25.0	9 510 390 069	9 510 390 063	230	3000	134.1	116.0	-16	-12
28.0	9 510 390 070	9 510 390 064	210	2800	137.1	119.0	-16	-12
32.0	9 510 390 071	9 510 390 065	180	2800	141.6	123.5	-16	-12
36.0	9 510 390 072	9 510 390 066	160	2600	146.1	129.9	-16	-12

* Contact factory for availability of units with no ordering number listed.

** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.




Ordering code
AZPN - X X - □ □ □ Q R 12 MB

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
					A	B	C	Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
20.0	9 510 390 079	9 510 390 073	230	3000	115.4	58.1	58.1	-16	-10
22.0	9 510 390 080	9 510 390 074	230	3000	118.4	59.6	59.6	-16	-10
25.0	9 510 390 081	9 510 390 075	230	3000	121.4	61.1	61.1	-20	-12
28.0	9 510 390 082	9 510 390 076	210	2800	124.4	62.6	62.6	-20	-12
32.0	9 510 390 083	9 510 390 077	180	2800	128.5	64.8	64.8	-20	-12
36.0	9 510 390 084	9 510 390 078	160	2600	133.0	67.1	67.1	-20	-12


* Contact factory for availability of units with no ordering number listed.

** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.



VIEW A-A.

Features	Details
Shaft	3/4" keyed
Front Cover	SAE A 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPN - X X - □ □ □ □ Q R 12 MA

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B		
20.0	9 510 390 128	9 510 390 122	230	3000	115.4	58.1	-16	-12
22.0	9 510 390 129	9 510 390 123	230	3000	118.4	59.6	-16	-12
25.0	9 510 390 130	9 510 390 124	230	3000	121.4	61.1	-16	-12
28.0	9 510 390 131	9 510 390 125	210	2800	124.4	62.6	-16	-12
32.0	9 510 390 132	9 510 390 126	180	2800	128.5	64.8	-16	-12
36.0	9 510 390 133	9 510 390 127	160	2600	133.0	67.1	-16	-12

* Contact factory for availability of units with no ordering number listed.


** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code****AZPN - X X - □ □ □ □ R R 12 MB**

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
					A	B	C	Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
20.0	9 510 390 031	9 510 390 025	230	3000	117.7	58.1	58.1	-16	-10
22.0	9 510 390 032	9 510 390 026	230	3000	120.7	59.6	59.6	-16	-10
25.0	9 510 390 033	9 510 390 027	230	3000	123.7	61.1	61.1	-20	-12
28.0	9 510 390 034	9 510 390 028	210	2800	126.7	62.6	62.6	-20	-12
32.0	9 510 390 035	9 510 390 029	180	2800	130.8	64.8	64.8	-20	-12
36.0	9 510 390 036	9 510 390 030	160	2600	135.3	67.1	67.1	-20	-12

* Contact factory for availability of units with no ordering number listed.

** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	9t spline
Front Cover	SAE A 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports

Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPN - X X - □ □ □ R R 12 MA

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B		
20.0	9 510 390 043	9 510 390 037	230	3000	134.1	116.0	-16	-12
22.0	9 510 390 044	9 510 390 038	230	3000	131.1	120.9	-16	-12
25.0	9 510 390 045	9 510 390 039	230	3000	140.1	122.0	-16	-12
28.0	9 510 390 046	9 510 390 040	210	2800	143.1	125.0	-16	-12
32.0	9 510 390 047	9 510 390 041	180	2800	147.6	129.5	-16	-12
36.0	9 510 390 048	9 510 390 042	160	2600	152.1	135.9	-16	-12

* Contact factory for availability of units with no ordering number listed.


** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code****AZPN - X X - □ □ □ D C 12 MB**


Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
	L	R			A	B	C	Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
20.0	9 510 390 007	9 510 390 001	230	3000	109.8	52.1	52.1	-16	-10
22.0	9 510 390 008	9 510 390 002	230	3000	114.7	53.6	53.6	-16	-10
25.0	9 510 390 009	9 510 390 003	230	3000	115.8	55.1	55.1	-20	-12
28.0	9 510 390 010	9 510 390 004	210	2800	118.8	56.6	56.6	-20	-12
32.0	9 510 390 011	9 510 390 005	180	2800	123.3	58.8	58.8	-20	-12
36.0	9 510 390 012	9 510 390 006	160	2600	129.7	61.1	61.1	-20	-12

* Contact factory for availability of units with no ordering number listed.

** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	13t spline
Front Cover	SAE B 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPN - X X - □ □ □ D C 12 MA


Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B		
20.0	9 510 390 019	9 510 390 013	230	3000	128.1	110.0	-16	-12
22.0	9 510 390 020	9 510 390 014	230	3000	131.1	114.9	-16	-12
25.0	9 510 390 021	9 510 390 015	230	3000	134.1	116.0	-16	-12
28.0	9 510 390 022	9 510 390 016	210	2800	137.1	119.0	-16	-12
32.0	9 510 390 023	9 510 390 017	180	2800	141.6	123.5	-16	-12
36.0	9 510 390 024	9 510 390 018	160	2600	146.1	129.9	-16	-12

* Contact factory for availability of units with no ordering number listed.

** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	13t spline
Front Cover	SAE A 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPN - X X - □ □ □ □ D R 12 MA

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B		
20.0	*	9 510 390 175	230	3000	133.6	116.0	-16	-12
22.0	9 510 390 188	9 510 390 176	230	3000	136.6	119.0	-16	-12
25.0	*	9 510 390 177	230	3000	139.6	124.0	-16	-12
28.0	*	9 510 390 178	210	2800	142.6	125.0	-16	-12
32.0	*	9 510 390 179	180	2800	147.1	129.5	-16	-12
36.0	*	9 510 390 180	160	2600	151.6	134.0	-16	-12

* Contact factory for availability of units with no ordering number listed.

** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.


**Ordering code**

AZPN - X X - □ □ □ □ D R 12 MB

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B	C		
20.0	*	*							
22.0	*	*							
25.0	*	*							
28.0	9 510 390 174	*	210	2800	124.7	62.8	62.8	-20	-12
32.0	*	9 510 390 173	180	2800	129.3	64.8	64.8	-20	-12
36.0	*	9 510 390 190	160	2600	135.7	67.1	67.1	-20	-12

* Contact factory for availability of units with no ordering number listed.


** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code****AZPN - X X - □ □ □ X R 12 MB-S0075**

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
					A	B	C	Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
20.0	9 510 390 116	9 510 390 110	230	3000	115.8	58.1	58.1	-16	-10
22.0	9 510 390 117	9 510 390 111	230	3000	120.7	59.6	59.6	-16	-10
25.0	9 510 390 118	9 510 390 112	230	3000	121.8	61.1	61.1	-20	-12
28.0	9 510 390 119	9 510 390 113	210	2800	124.8	62.6	62.6	-20	-12
32.0	9 510 390 120	9 510 390 114	180	2800	129.3	64.8	64.8	-20	-12
36.0	9 510 390 121	9 510 390 115	160	2600	135.7	67.1	67.1	-20	-12


* Contact factory for availability of units with no ordering number listed.

** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.



VIEW A-A

Features	Details
Shaft	Taper keyed
Front Cover	SAE A 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPN - X X - □ □ □ X R 12 MA-S0075

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		Inlet Port ** (SAE O-Ring BOSS)	Outlet Port (SAE O-Ring BOSS)
	L	R			A	B		
20.0	9 510 390 140	9 510 390 134	230	3000	134.1	116.0	-16	-12
22.0	9 510 390 141	9 510 390 135	230	3000	137.1	120.9	-16	-12
25.0	9 510 390 142	9 510 390 136	230	3000	140.1	122.0	-16	-12
28.0	9 510 390 143	9 510 390 137	210	2800	143.1	125.0	-16	-12
32.0	9 510 390 144	9 510 390 138	180	2800	147.6	129.5	-16	-12
36.0	9 510 390 145	9 510 390 139	160	2600	152.1	135.9	-16	-12

* Contact factory for availability of units with no ordering number listed.


** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code****AZPN - X X - □ □ □ D C 20 MB**

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			
					A	B		
25.0	0 510 725 377	0 510 725 057	230	3000	55.0	116.1		
28.0		0 510 725 058	210	2800	56.5	119.1		
36.0	0 510 725 363		160	2600	61.0	128.1		

* Contact factory for availability of units with no ordering number listed.


** Refer to page 46 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code**

AZPN - X X - □ □ □ □ C B 20 MB

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			
	L	R			A	B		
20.0	0 510 625 335	0 510 625 035	230	3000	52.0	109.8		
25.0	0 510 725 352	0 510 725 047	230	3000	55.0	115.8		
28.0	0 510 725 364	0 510 725 055	210	2800	56.5	118.8		
32.0	0 510 725 353	0 510 725 048	180	2800	59.0	123.3		

* Contact factory for availability of units with no ordering number listed.

**Ordering code****AZPN - X X - □ □ □ □ N M 20 MB**


Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]	
	L	R			A	B
25.0		0 510 715 006	230	3000	55.0	109.1
32.0		0 510 715 007	180	2800	59.0	116.6

* Contact factory for availability of units with no ordering number listed.

Ordering Code (G Series Pump)

A	Z	P	G	-	22	-	045	-	R	D	C	12	M	B
Function														
P = Pump														
Size (G)														
1.99 in ³ (32.6 cm ³) = 032														
2.20 in ³ (36.0 cm ³) = 036														
2.75 in ³ (45.0 cm ³) = 045														
3.42 in ³ (56.0 cm ³) = 056														
3.84 in ³ (63.0 cm ³) = 063														
Direction of rotation														
Right = R														
Left = L														
Drive shafts														
Matching front flange														
C	Conical 1:5 (Tapered key)		B		B	Square flange Pilot Ø 105 mm			20	Rectangular flange				
S	Conical 1:5 for flange A (Tapered key)		A		O	Square flange Pilot Ø 50.78 mm			30	Rectangular flange				
H	Conical 1:8 (Tapered key)		O		C	SAE B 2-bolt			07	Split flange SAE Code 61 Metric bolts				
N	Dog (Tang)		M		M	Transmission flange Pilot Ø 52 mm with O-ring			40	Split flange SAE Code 61 UNC bolts				
Q	Cylindrical (Straight Key) SAE B 7/8"		C		A	Outrigger bearing Pilot Ø 105 mm (outboard bearing)			12	Thread (UN-23) SAE O-Ring BOSS				
D	Spline shaft SAE B 13T		C											
F	Spline shaft DIN 5482 B17x14		B											

Note: Consult Factory for Availability



N Series Pump Product Index

(Reference page 43 for ordering code designators)

AZPF-XX-XXXX - - - MB

Page Number	Shaft Ordering code	Mounting Type	Flange	Port Ports	Orientation
73	AZPG-22-XXXXDC12MB	D	C	12	side
74	AZPG-22-XXXXDC12MA	D	C	12	rear
75	AZPG-22-XXXXQC12MB	Q	C	12	side
76	AZPG-22-XXXXQC12MA	Q	C	12	rear
77	AZPG-22-XXXXDC40MB	D	C	40	side
78	AZPG-22-XXXXQC40MB	Q	C	40	side

G Series Performance Ratings

Size		32	36	45	56	63
Displacement:	cm ³ /rev	32	36	45	56	63
	cu in/rev	1.95	2.20	2.75	3.42	3.84
Range Speed:	Min RPM	400	400	400	400	400
	Max RPM	2800	2800	2600	2300	2300
Pressure - Rated: p ₁	(Bar)	250	250	250	195	170
	(PSI)	3625	3625	3625	2828	2465
Intermittent: p ₂	(Bar)	280	280	280	225	200
	(PSI)	4060	4060	4060	3263	2900
Max Peak: p ₃	(Bar)	300	300	300	250	230
	(PSI)	4350	4350	4350	3625	3335
Inlet Pressure:	Continuous	0.7 - 3.0 bar absolute (9in Hg vacuum to 29 PSIG)				
	Intermittent	0.1 - 10 bar absolute (26in Hg vacuum to 130 PSIG)				

G Series Pumps**SAE O-Ring BOSS - Standard Porting**

Displacement	Side Ports		Rear Port	
	Inlet	Outlet	Inlet	Outlet
32	-20	-16	-20	-16
36	-20	-16	-20	-16
45	-20	-16	-20	-16
56	-24	-20	-20	-16
63	-24	-20	-20	-16

SAE Porting - Specifications and Dimensions

per SAE J1926/1

Dash Size	Thread Size (in)
-2	5/16-24 UNF-2B
-3	3/8-24 UNF-2B
-4	7/16-20 UNF-2B
-5	1/2-20 UNF-2B
-6	9/16-18 UNF-2B
-8	3/4-16 UNF-2B
-10	7/8-14 UNF-2B
-12	1-1/16-12 UN-2B
-14	1-3/16-12 UN-2B
-16	1-5/16-12 UN-2B
-20	1-5/8-12 UN-2B
-24	1-7/8-12 UN-2B
-32	2-1/2-12 UN-2B

Split Flange SAE Porting - Specifications and Dimensions

per SAE J518 (Code 61)

Nominal Flange Size	Flange Dash Size	Port Diamenter (max)	
		Inches	mm
1/2	-8	0.50	13
3/4	-12	0.75	19
1	-16	1.00	25
1-1/4	-20	1.25	32
1-1/2	-24	1.50	38
2	-32	2.00	51

Note: Ratings represent units incorporating SAE O-Ring BOSS threaded ports. Pressure ratings may differ for other types of ports.


Diagrams

Size **G**


$v = 35 \text{ mm}^2/\text{s}$, $T = 50^\circ\text{C}$





Unit Conversions


Pressure: $\text{psi} = \text{bar} \times 14.7$
 Torque: $\text{ft-lbs} = (\text{Nm}) \times .738$
 Power: $\text{hp} = (\text{kW}) \times 1.341$
 Volume: $\text{in}^3 = (\text{cc}) \times 16.39$
 $\text{gpm} = (\text{LPM}) \times .2642$



32 cm³/rev




36 cm³/rev**45 cm³/rev****56 cm³/rev****63 cm³/rev**

**Ordering code****AZPG - 2 2 - □ □ □ D C 12 MB**


Displacement [cm ³ /rev]	L	Ordering-Number *	R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]					
						A	B	C	Inlet Port** (SAE O-Ring BOSS)	Outlet Port** (SAE O-Ring BOSS)	
32.0		9 510 490 014		9 510 490 004	250	2800	139.2	70.3	70.3	-20	-16
36.0		9 510 490 015		9 510 490 005	250	2800	142.5	72.0	72.0	-20	-16
45.0		9 510 490 017		9 510 490 007	250	2600	149.9	75.7	75.7	-24	-20
56.0		9 510 490 019		9 510 490 009	195	2300	159.0	80.2	80.2	-24	-20
63.0		9 510 490 020		9 510 490 010	170	2300	164.8	83.1	83.1	-24	-20

* Contact factory for availability of units with no ordering number listed.

** Refer to page 70 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	13t spline
Front Cover	SAE B 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports



Clockwise
Inlet and outlet port changed



Counter-Clockwise
As shown in drawing


Ordering code

AZPG - 2 2 - D C 12 MA


Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		Inlet Port** (SAE O-Ring BOSS)	Outlet Port** (SAE O-Ring BOSS)
	L	R			A	B		
32.0	9 510 490 074	9 510 490 064	250	2800	149.4	138.7	-20	-16
36.0	9 510 490 075	9 510 490 065	250	2800	152.8	142.0	-20	-16
45.0	9 510 490 077	9 510 490 067	250	2600	160.2	149.4	-20	-16
56.0	9 510 490 079	9 510 490 069	195	2300	169.2	158.5	-20	-16
63.0	9 510 490 080	9 510 490 070	170	2300	175.1	164.3	-20	-16

* Contact factory for availability of units with no ordering number listed.

** Refer to page 70 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	7/8 keyed
Front Cover	SAE B2-bolt
Ports	SAE ORB
Rear Cover	Standard



Clockwise
Inlet and outlet port changed

Counter-Clockwise
As shown in drawing


Ordering code

AZPG - 2 2 - □ □ □ □ Q C 12 MB


Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
					A	B	C	Inlet Port** (SAE O-Ring BOSS)	Outlet Port** (SAE O-Ring BOSS)
32.0	9 510 490 034	9 510 490 024	250	2800	139.2	70.3	70.3	-20	-16
36.0	9 510 490 035	9 510 490 025	250	2800	142.5	72.0	72.0	-20	-16
45.0	9 510 490 037	9 510 490 027	250	2600	149.9	75.7	75.7	-24	-20
56.0	9 510 490 039	9 510 490 029	195	2300	159.0	80.2	80.2	-24	-20
63.0	9 510 490 040	9 510 490 030	170	2300	164.8	83.1	83.1	-24	-20

* Contact factory for availability of units with no ordering number listed.

** Refer to page 70 for SAE O-Ring Boss Specifications and Dimensions.



Features	Details
Shaft	7/8" key
Front Cover	SAE B 2-bolt
Ports	SAE ORB
Rear Cover	Rear ports



Clockwise
Inlet and outlet port changed

Counter-Clockwise
As shown in drawing


Ordering code

AZPG - 2 2 - Q C 12 MA

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		Inlet Port** (SAE O-Ring BOSS)	Outlet Port** (SAE O-Ring BOSS)
	L	R			A	B		
32.0	9 510 490 114	9 510 490 104	250	2800	149.4	138.7	-20	-16
36.0	9 510 490 115	9 510 490 105	250	2800	152.8	142.0	-20	-16
45.0	9 510 490 117	9 510 490 107	250	2600	160.2	149.4	-20	-16
56.0	9 510 490 119	9 510 490 109	195	2300	169.2	158.5	-20	-16
63.0	9 510 490 120	9 510 490 110	170	2300	175.1	164.3	-20	-16

* Contact factory for availability of units with no ordering number listed.

** Refer to page 70 for SAE O-Ring Boss Specifications and Dimensions.




Ordering code
AZPG - 2 2 - □ □ □ D C 40 MB

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]					Port Size Per SAE J 518		
					A	B	C	Inlet Port**	Outlet Port**			
32.0	9 510 490 054	9 510 490 044	250	2800	139.2	70.3	70.3	-16	-12			
36.0	9 510 490 055	9 510 490 045	250	2800	142.5	72.0	72.0	-16	-12			
45.0	9 510 490 057	9 510 490 047	250	2600	149.9	75.7	75.7	-20	-16			
56.0	9 510 490 059	9 510 490 049	195	2300	159.0	80.2	80.2	-24	-20			
63.0	9 510 490 060	9 510 490 050	170	2300	164.8	83.1	83.1	-24	-20			

* Contact factory for availability of units with no ordering number listed.

** Refer to page 70 for SAE Split flange porting Specifications and Dimensions.

**Ordering code**

AZPG - 2 2 - □ □ □ □ Q C 40 MB

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]					Port Size Per SAE J 518
	L	R			A	B	C	Inlet Port**	Outlet Port**	
32.0	9 510 490 094	9 510 490 084	250	2800	139.2	70.3	70.3	-16	-12	
36.0	9 510 490 095	9 510 490 085	250	2800	142.5	72.0	72.0	-16	-12	
45.0	9 510 490 097	9 510 490 087	250	2600	149.9	75.7	75.7	-20	-16	
56.0	9 510 490 099	9 510 490 089	195	2300	159.0	80.2	80.2	-24	-20	
63.0	9 510 490 100	9 510 490 090	170	2300	164.8	83.1	83.1	-24	-20	

* Contact factory for availability of units with no ordering number listed.

** Refer to page 70 for SAE Split flange porting Specifications and Dimensions.

Notes

Ordering code

External Gear Pumps – Multiple Pumps

AZ	P	GGFF	-	<input type="checkbox"/>	-	032 / 022 / 016 / 005	R	R	R	12	12	12	M	B
Function														
P = Pump														
Model **														
F = 4.0 ... 28.0 cm ³ /rev														
N = 20.0 ... 36.0 cm ³ /rev														
G = 32.0 ... 63.0 cm ³ /rev														
Series														
1x = Standard bearing														
2x = Reinforced bearing														
Size														
Based on available sizes per series														
Direction of rotation														
Right = R														
Left = L														
Drive shafts														
Front cover														
Port connections														
Model F:														
Q Cylindrical (Straight Way) SAE A 5/8"			C SAE B 2-bolt flange Pilot Ø 101.6 mm 		12 Thread (UN-2B) SAE O-Ring BOSS 									
P Spline Shaft SAE 11T				R SAE A 2-bolt flange Ø 82.55 mm 										
R Multiple spline shaft SAE A 5/8" 9T														
Model N:														
P Spline Shaft SAE 11T				R SAE A 2-bolt flange Ø 82.55 mm 		12 Thread (UN-2B) SAE O-Ring BOSS 								
D Multiple spline shaft SAE B 13T				C SAE B 2-bolt flange Pilot Ø 101.6 mm 										
Q SAE 3/4" Keyed, Short														
Model G:														
D Multiple spline shaft SAE B 13T			C SAE B 2-bolt flange Pilot Ø 101.6 mm 		12 Thread (UN-2B) SAE O-Ring BOSS 									
Q Cylindrical (Straight Key) SAE B 7/8"					40 Split Flange SAE Code 61 UNC bolts 									

* Contact factory for availability of units with no ordering number listed

** Refer to page 18 for SAE O-Ring Boss Specifications and dimensions

F + F
F + F + F
N + F


N Series Pump Product Index

(Reference page 43 for ordering code designators)


AZPF-XX-XXXX - - - MB



Page Number	Ordering code	Shaft Type	Mounting Flange	Ports	Port Orientation
82	AZPFF-XX-XXX/XXXXRR1212MB	R	R	12	side
83	AZPFF-XX-XXX/XXXXQR1212MB	Q	R	12	side
84	AZPFF-XX-XXX/XXXXPR1212MB	P	R	12	side
85	AZPFF-XX-XXX/XXXXCB2020MB	C	B	20	side
86	AZPFF-XX-XXX/XXXXFB2020MB	F	B	20	side
87	AZPFF-XX-XXX/XXXXNM2020MB	N	M	20	side
88	AZPFF-XX-XXX/XXXXRR2020MB	R	R	20	side
89	AZPFF-XX-XXX/XXXXSA2020MB	S	A	20	side
90	AZPFFF-XX-XXX/XXX/XXXXFB202020MB	F	B	20	side
91	AZPNF-XX-XXX/XXXXDC2020KB	D	C	20	side



Features	Details
Shaft	9t spline
Front Cover	SAE A 2-bolt
Ports	SAE ORB
Rear Cover	Standard



Clockwise
As shown in drawing

Counter-Clockwise
Inlet and outlet port changed


Ordering code

AZPFF - X X - □ □ □ - □ □ □ □ R R 12 12 MB

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
					A1	A2	B	Inlet Port** (SAE O-Ring BOSS)	Outlet Port** (SAE O-Ring BOSS)
008 / 008	*	9 510 290 034	250	3000	43.2	119.5	166.2	-12 / -12	-8 / -8
011 / 005	*	9 510 290 142	210	3000	45.7	122.4	170.9	-12 / -10	-10 / -8
014 / 005	*	9 510 290 143	210	3000	48.2	127.4	175.9	-12 / -10	-10 / -8
014 / 008	*	9 510 290 144	210	3000	48.2	129.0	176.2	-12 / -12	-10 / -10

* Contact factory for availability of units with no ordering number listed.


** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.

**Ordering code****AZPFF - X X - □ □ □ / □ □ □ Q R 12 12 MB**

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
					A1	A2	B	Inlet Port** (SAE O-Ring BOSS)	Outlet Port** (SAE O-Ring BOSS)
008 / 004	*	9 510 290 138	210	3000	43.2	155.0	161.5	-12 / -10	-10 / -8
008 / 008	*	9 510 290 137	210	3000	43.2	155.0	166.2	-12 / -12	-10 / -10
011 / 004	*	9 510 290 139	210	3000	45.7	121.3	164.6	-12 / -10	-10 / -8
011 / 005	*	9 510 290 140	210	3000	45.7	122.5	170.9	-12 / -10	-10 / -8
011 / 008	*	9 510 290 141	210	3000	45.7	124.6	171.2	-12 / -12	-10 / -10
014 / 005	*	9 510 290 052	210	3000	48.2	127.4	175.9	-12 / -10	-10 / -8

* Contact factory for availability of units with no ordering number listed.

** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.


**Ordering code**

AZPFF - X X - □ □ □ - □ □ □ □ PR 12 12 MB

Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]				
					A1	A2	B	Inlet Port** (SAE O-Ring BOSS)	Outlet Port** (SAE O-Ring BOSS)
016 / 016	*	9 510 290 108	210	3000	49.9	139.6	193.0	-16 / -16	-10 / -10

* Contact factory for availability of units with no ordering number listed.

** Refer to page 19 for SAE O-Ring Boss Specifications and Dimensions.


**Ordering code**

AZPFF - X X - □ □ □ / □ □ □ C B 20 20 MB

+ AZPFF - X X - □ □ □ / □ □ □ C B 20 20 MB - S0012

Displacement [cm ³ /rev]	Ordering-Number *	R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		
					A	B	C
014 / 008	0 510 565 364	0 510 565 012	280	3000	47.5	141.5	188.1
014 / 011	0 510 565 353	0 510 565 033	280	3000	47.5	145.3	193.1
014 / 014		0 510 565 037	280	3000	47.5	145.8	198.1
019 / 05.5		0 510 665 067	230/280	3000	47.5	147.8	192.4
019 / 008	0 510 665 325	0 510 665 024	230/280	3000	47.5	149.9	196.5
019 / 011	0 510 665 326		230/280	3000	47.5	153.9	201.5
019 / 016	0 510 665 327	0 510 665 053	230	3000	47.5	154.2	209.9
019 / 019	0 510 665 400	0 510 665 025	230/190	3000	47.5	154.2	214.9
22.5 / 008		0 510 765 023+	230/280	3000	61.0	167.2	213.9
22.5 / 011	0 510 765 320+		230/280	3000	61.0	171.5	218.2
22.5 / 016	0 510 465 340+				61.0	171.6	227.3
22.5 / 22.5		0 510 765 012+	230/160	3000	61.0	185.2	249.7


* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPFF - X X - □ □ □ / □ □ □ F B 20 20 MB


Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		
	L	R			A	B	C
019 / 011	0 510 665 375		230/280	3000	47.5	153.7	201.5
019 / 019	0 510 665 420	0 510 665 097	230/190	3000	47.5	154.2	214.9
022 / 05.5	0 510 765 317	0 510 665 022	210/280	2500	61.1	165.2	209.8
022 / 008	0 510 765 331		210/280	2500	61.1	167.3	213.9

* Contact factory for availability of units with no ordering number listed.

**Ordering code****AZPFF - X X - □ □ □ / □ □ □ N M 20 20 MB**


Displacement [cm ³ /rev]	Ordering-Number * L	Ordering-Number * R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		
					A	B	C
05.5 / 004	0 510 365 314	0 510 365 010	280	4000	38.6	121.6	157.9
008 / 004		0 510 465 012	280	4000	40.7	125.7	162.0
008 / 05.5	0 510 465 346	0 510 465 008	280	4000	40.7	126.9	164.5
011 / 004	0 510 565 329	0 510 565 015	280	3500	44.5	130.7	167.0
011 / 05.5		0 510 565 016	280	3500	44.5	131.9	169.5
011 / 008	0 510 565 379	0 510 565 078	280	3500	44.5	134.0	173.6
016 / 016	0 510 565 339	0 510 665 030	280/230	3000	45.0	146.7	195.4
022 / 008	0 510 765 312		210/280	3000	52.6	152.8	194.0

* Contact factory for availability of units with no ordering number listed.

**Ordering code****AZPFF - XX - □□□ / □□□ R R 20 20 MB**

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		
	L	R			A	B	C
011 / 004		0 510 565 022	280	3500	47.0	133.2	176.5
011 / 05.5		0 510 565 023	280	3500	47.0	134.4	179.0
014 / 011	0 510 565 346		280	3000	47.0	147.8	191.1


* Contact factory for availability of units with no ordering number listed.

**Ordering code**

AZPFF - X X - □ □ □ / □ □ □ S A 20 20 MB


Displacement [cm ³ /rev]	Ordering-Number *	R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		
					A	B	D
004 / 004	0 510 255 300		280	4000	71.3	153.0	197.0
05.5 / 004	0 510 355 301		280	4000	72.6	155.5	199.5
008 / 05.5	0 510 455 300	0 510 455 001	280	4000	74.6	160.8	205.1
008 / 008	0 510 455 301	0 510 455 002	280	4000	74.6	163.0	210.2
011 / 05.5	0 510 555 300	0 510 555 001	280	3500	79.0	165.8	211.1
011 / 008	0 510 555 301	0 510 555 002	280	3500	79.0	168.0	215.2
011 / 011	0 510 555 302	0 510 555 003	280	3500	79.0	172.3	220.2
016 / 004	0 510 655 300	0 510 655 001	280	3000	79.0	173.0	217.0
016 / 05.5	0 510 655 301	0 510 655 002	280	3000	79.0	174.2	219.5
016 / 008	0 510 655 302	0 510 655 003	280	3000	79.0	176.3	223.6
016 / 011	0 510 655 303	0 510 655 004	280	3000	79.0	180.7	228.6
016 / 016	0 510 655 304	0 510 655 005	280	3000	79.0	180.7	237.0

* Contact factory for availability of units with no ordering number listed.

**Ordering code****AZPFF - X X - □ □ □ / □ □ □ □ □ □ □ F B 20 20 20 MB**

Displacement [cm ³ /rev]	Ordering-Number *		Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]			
	L	R			A	B	C	D
011 / 004 / 004	0 510 565 371		280	3500	47.0	133.2	214.9	262.5
014 / 004 / 008	0 510 565 408		280	3000	47.5	138.2	223.2	272.5
016 / 004 / 004	0 510 665 379		280	3000	47.5	141.5	223.3	270.0
016 / 05.5 / 05.5		0 510 656 061	280	3000	47.5	142.8	227.0	277.5
016 / 05.5 / 05.5	0 510 665 416		280	3000	47.5	142.8	227.0	277.5
016 / 011 / 004	0 510 665 372		280/210/210	3000	47.5	148.7	234.9	282.0
016 / 016 / 011	0 510 665 371		280/120/120	3000	47.5	149.2	250.4	302.0

* Contact factory for availability of units with no ordering number listed.

**Ordering code****AZPNF - X X - □ □ □ / □ □ □ D C 20 20 KB**

Displacement [cm ³ /rev]	L	Ordering-Number *	R	Max. operating pressure [bar]	Max. rotation speed [min ⁻¹]	Dimension [mm]		
						A	B	C
025 / 014		0 510 766 010		250	3000	55.1	155.1	209.2
028 / 016	0 510 767 311		0 510 767 018	230	2800	56.5	158.0	215.6
032 / 014			0 510 768 021	200/250	2800	59.0	162.6	216.7

* Contact factory for availability of units with no ordering number listed.

Seal Kits (reference Fig. 15)

Example Model Code: AZPF – 12 – 008 RRR 12MB

Model Code Designator for Shaft

Model Code Designator for Seal

Model Code For Shaft		Shaft Description	Model Code For Seal	Seal Material	Seal Pos. 800 & Pos. 3	Sets of Seals Sps. 800	Shaft Seal Pos. 3	O-ring Pos. 31
F Series Pump	R	SAE 9T Spline	M	NBR	1506635001	1517010152	1510283035	—
			P	FPM	—	1517010193	1510283027	—
			K	NBR W/FPM SHAFT SEAL	—	1517010152	1510283027	—
	Q	5/8" Straight Key	M	NBR	1506635001	1517010152	1510283035	—
			P	FPM	—	1517010193	1510283027	—
			K	NBR W/FPM SHAFT SEAL	—	1517010152	1510283027	—
	P	SAE 11T Spline	M	NBR	1506635003	1517010152	1510283037	—
			P	FPM	—	1517010193	1510283044	—
			K	NBR W/FPM SHAFT SEAL	—	1517010152	1510283044	—
	C	1:5 Tapered Key	M	NBR	1506635001	1517010152	1510283038	—
			P	FPM	—	1517010193	1510283027	—
			K	NBR W/FPM SHAFT SEAL	—	1517010152	1510283027	—
	S	1:5 Tapered for Flange A	M	NBR	—	1517010152	1510283009	—
			P	FPM	—	1517010193	1510283015	—
			K	NBR W/FPM SHAFT SEAL	—	1517010152	1510283015	—
	H	1:8 Tapered Key	M	NBR	1506635001	1517010152	1510283008	—
			P	FPM	—	1517010193	1510283027	—
			K	NBR W/FPM SHAFT SEAL	—	1517010152	1510283027	—
	N	Dog	M	NBR	1506635001	1517010152	1510283008	1900210145
			P	FPM	—	1517010193	1510283027	1900210145
			K	NBR W/FPM SHAFT SEAL	—	1517010152	1510283027	—
	A	18mm Straight Key	M	NBR	1506635003	1517010152	1510283037	—
			P	FPM	—	1517010193	1510283027	—
			K	NBR W/FPM SHAFT SEAL	—	1517010152	1510283027	—
	F	Din 5482 B17x14 Spline	M	NBR	1506635001	1517010152	1510283008	—
			P	FPM	—	1517010193	1510283027	—
			K	NBR W/FPM SHAFT SEAL	—	1517010152	1510283027	—
	P	SAE 11T Spline	M	NBR	1509635001	1517010194	1510283023	—
			P	FPM	—	1517010197	1510283028	—
			K	NBR W/FPM SHAFT SEAL	—	1517010194	1510283028	—
	Q	SAE 3/4" Keyed Shaft	M	NBR	1509635001	1517010194	1510283023	—
			P	FPM	—	1517010197	1510283028	—
			K	NBR W/FPM SHAFT SEAL	—	1517010194	1510283028	—
	R	SAE 9T Spline	M	NBR	1509635001	1517010194	1510283023	—
			P	FPM	—	1517010197	1510283028	—
			K	NBR W/FPM SHAFT SEAL	—	1517010194	1510283028	—
	D	SAE 13T Spline	M	NBR	1509635001	1517010194	1510283023	—
			P	FPM	—	1517010197	1510283028	—
			K	NBR W/FPM SHAFT SEAL	—	1517010194	1510283028	—
	Q-S0022	SAE 3/4" Keyed, Long	M	NBR	1509635001	1517010194	1510283023	—
			P	FPM	—	1517010197	1510283028	—
			K	NBR W/FPM SHAFT SEAL	—	1517010194	1510283028	—
	C	1:5 Tapered Key	M	NBR	1509635001	1517010194	1510283023	—
			P	FPM	—	1517010197	1510283028	—
			K	NBR W/FPM SHAFT SEAL	—	1517010194	1510283028	—
	N	Dog (tang)	M	NBR	1509635001	1517010194	1510283023	—
			P	FPM	—	1517010197	1510283028	—
			K	NBR W/FPM SHAFT SEAL	—	1517010194	1510283028	—
	H	1:8 Tapered Key	M	NBR	1509635001	1517010194	1510283023	—
			P	FPM	—	1517010197	1510283028	—
			K	NBR W/FPM SHAFT SEAL	—	1517010194	1510283028	—
	A	ISO Keyed, 18mm	M	NBR	1509635001	1517010194	1510283023	—
			P	FPM	—	1517010197	1510283028	—
			K	NBR W/FPM SHAFT SEAL	—	1517010194	1510283028	—
	D	SAE B - 13T Spline	M	NBR	—	1517010190	1510283010	—
			P	FPM	—	1517010203*	1510283068	—
			K	NBR W/FPM SHAFT SEAL	—	1517010190	1510283068	—
	Q	SAE 7/8" Keyed Shaft	M	NBR	—	1517010190	1510283010	—
			P	FPM	—	1517010203*	1510283025	—
			K	NBR W/FPM SHAFT SEAL	—	1517010190	1510283025	—
	C	1:5 Tapered Key	M	NBR	—	1517010190	1510283010	—
			P	FPM	—	—	—	—
			K	NBR W/FPM SHAFT SEAL	—	1517010190	1510283025	—
	S	1:5 Tapered Key (flange A)	M	NBR	—	1517010190	1510283010	—
			P	FPM	—	—	—	—
			K	NBR W/FPM SHAFT SEAL	—	—	—	—
	H	1:8 Tapered Key	M	NBR	—	1517010190	1510283010	—
			P	FPM	—	—	—	—
			K	NBR W/FPM SHAFT SEAL	—	—	—	—
	N	Dog (tang)	M	NBR	—	1517010190	1510283010	—
			P	FPM	—	—	—	—
			K	NBR W/FPM SHAFT SEAL	—	—	—	—
	F	DIN 5482 B17x14 Spline	M	NBR	—	1517010190	1510283014	—
			P	FPM	—	—	—	—
			K	NBR W/FPM SHAFT SEAL	—	—	—	—

* only housing seal are in FPM




Fig. 15

Part Number Index

External Gear Pumps – Multiple Pumps

Part Number	Page						
0 510 215 006.....	37	0 510 515 019.....	41	0 510 625 028.....	31	0 510 765 023.....	85
0 510 215 007.....	41	0 510 515 309.....	39	0 510 625 029.....	31	0 510 765 312.....	87
0 510 215 009.....	39	0 510 515 310.....	37	0 510 625 035.....	66	0 510 765 317.....	86
0 510 215 306.....	37	0 510 515 311.....	41	0 510 625 047.....	36	0 510 765 320.....	85
0 510 215 307.....	41	0 510 515 316.....	39	0 510 625 052.....	36	0 510 765 331.....	86
0 510 215 309.....	39	0 510 515 337.....	40	0 510 625 314.....	32	0 510 766 010.....	91
0 510 225 006.....	32	0 510 515 338.....	40	0 510 625 315.....	32	0 510 767 018.....	91
0 510 225 007.....	33	0 510 515 340.....	41	0 510 625 316.....	33	0 510 767 311.....	91
0 510 225 008.....	34	0 510 525 009.....	32	0 510 625 317.....	33	0 510 768 021.....	91
0 510 225 013.....	31	0 510 525 010.....	33	0 510 625 318.....	34	9 510 290 004.....	23
0 510 225 015.....	36	0 510 525 011.....	34	0 510 625 319.....	34	9 510 290 005.....	23
0 510 225 306.....	32	0 510 525 012.....	34	0 510 625 329.....	31	9 510 290 015.....	23
0 510 225 307.....	33	0 510 525 018.....	32	0 510 625 330.....	31	9 510 290 017.....	23
0 510 225 308.....	34	0 510 525 019.....	31	0 510 625 335.....	66	9 510 290 018.....	23
0 510 225 314.....	31	0 510 525 020.....	31	0 510 645 002.....	42	9 510 290 021.....	25
0 510 245 001.....	42	0 510 525 024.....	35	0 510 645 003.....	43	9 510 290 022.....	25
0 510 245 300.....	42	0 510 525 030.....	33	0 510 645 004.....	42	9 510 290 023.....	25
0 510 255 300.....	89	0 510 525 039.....	36	0 510 645 005.....	43	9 510 290 024.....	25
0 510 315 004.....	37	0 510 525 040.....	36	0 510 645 300.....	42	9 510 290 025.....	25
0 510 315 005.....	41	0 510 525 311.....	32	0 510 655 001.....	89	9 510 290 034.....	82
0 510 315 006.....	39	0 510 525 312.....	33	0 510 655 002.....	89	9 510 290 036.....	23
0 510 315 007.....	38	0 510 525 313.....	34	0 510 655 003.....	89	9 510 290 037.....	23
0 510 315 304.....	37	0 510 525 314.....	34	0 510 655 004.....	89	9 510 290 038.....	23
0 510 315 305.....	41	0 510 525 319.....	32	0 510 655 005.....	89	9 510 290 039.....	23
0 510 315 307.....	39	0 510 525 323.....	35	0 510 655 300.....	89	9 510 290 040.....	23
0 510 325 006.....	32	0 510 525 324.....	31	0 510 655 301.....	89	9 510 290 044.....	25
0 510 325 007.....	33	0 510 525 325.....	31	0 510 655 302.....	89	9 510 290 045.....	25
0 510 325 008.....	34	0 510 525 328.....	33	0 510 655 303.....	89	9 510 290 046.....	25
0 510 325 013.....	31	0 510 545 001.....	42	0 510 655 304.....	89	9 510 290 047.....	25
0 510 325 018.....	36	0 510 545 002.....	43	0 510 656 061.....	90	9 510 290 048.....	25
0 510 325 306.....	32	0 510 545 003.....	43	0 510 665 022.....	86	9 510 290 052.....	83
0 510 325 307.....	33	0 510 545 300.....	42	0 510 665 024.....	85	9 510 290 056.....	23
0 510 325 308.....	34	0 510 545 302.....	43	0 510 665 025.....	85	9 510 290 057.....	27
0 510 325 313.....	31	0 510 555 001.....	89	0 510 665 030.....	87	9 510 290 058.....	27
0 510 345 001.....	42	0 510 555 002.....	89	0 510 665 053.....	85	9 510 290 059.....	27
0 510 345 300.....	42	0 510 555 003.....	89	0 510 665 067.....	85	9 510 290 060.....	27
0 510 355 301.....	89	0 510 555 300.....	89	0 510 665 097.....	86	9 510 290 061.....	27
0 510 365 010.....	87	0 510 555 301.....	89	0 510 665 325.....	85	9 510 290 062.....	27
0 510 365 314.....	87	0 510 555 302.....	89	0 510 665 326.....	85	9 510 290 063.....	27
0 510 415 005.....	37	0 510 565 012.....	85	0 510 665 327.....	85	9 510 290 064.....	27
0 510 415 006.....	41	0 510 565 015.....	87	0 510 665 371.....	90	9 510 290 065.....	27
0 510 415 313.....	37	0 510 565 016.....	87	0 510 665 372.....	90	9 510 290 066.....	27
0 510 415 314.....	41	0 510 565 022.....	88	0 510 665 375.....	86	9 510 290 067.....	27
0 510 415 316.....	39	0 510 565 023.....	88	0 510 665 379.....	90	9 510 290 068.....	27
0 510 415 328.....	40	0 510 565 033.....	85	0 510 665 400.....	85	9 510 290 069.....	27
0 510 425 009.....	32	0 510 565 037.....	85	0 510 665 416.....	90	9 510 290 070.....	27
0 510 425 010.....	33	0 510 565 078.....	87	0 510 665 420.....	86	9 510 290 071.....	27
0 510 425 011.....	34	0 510 565 329.....	87	0 510 715 004.....	41	9 510 290 072.....	27
0 510 425 020.....	31	0 510 565 339.....	87	0 510 715 006.....	67	9 510 290 075.....	24
0 510 425 021.....	35	0 510 565 346.....	88	0 510 715 007.....	67	9 510 290 076.....	24
0 510 425 027.....	36	0 510 565 353.....	85	0 510 715 008.....	40	9 510 290 077.....	24
0 510 425 307.....	32	0 510 565 364.....	85	0 510 715 016.....	37	9 510 290 078.....	24
0 510 425 308.....	33	0 510 565 371.....	90	0 510 715 306.....	39	9 510 290 079.....	24
0 510 425 309.....	34	0 510 565 379.....	87	0 510 715 307.....	41	9 510 290 080.....	24
0 510 425 314.....	31	0 510 565 408.....	90	0 510 715 320.....	40	9 510 290 081.....	24
0 510 425 315.....	35	0 510 615 005.....	39	0 510 725 030.....	32	9 510 290 082.....	24
0 510 445 001.....	42	0 510 615 006.....	37	0 510 725 031.....	34	9 510 290 083.....	24
0 510 445 300.....	42	0 510 615 007.....	41	0 510 725 047.....	66	9 510 290 084.....	24
0 510 455 001.....	89	0 510 615 008.....	41	0 510 725 048.....	66	9 510 290 085.....	24
0 510 455 002.....	89	0 510 615 009.....	38	0 510 725 055.....	66	9 510 290 086.....	24
0 510 455 300.....	89	0 510 615 010.....	39	0 510 725 057.....	65	9 510 290 087.....	24
0 510 455 301.....	89	0 510 615 023.....	40	0 510 725 058.....	65	9 510 290 088.....	24
0 510 465 008.....	87	0 510 615 314.....	37	0 510 725 062.....	33	9 510 290 089.....	24
0 510 465 012.....	87	0 510 615 315.....	41	0 510 725 077.....	31	9 510 290 090.....	24
0 510 465 340.....	85	0 510 615 317.....	39	0 510 725 084.....	36	9 510 290 091.....	26
0 510 465 346.....	87	0 510 615 318.....	39	0 510 725 330.....	32	9 510 290 092.....	26
0 510 515 004.....	37	0 510 615 321.....	41	0 510 725 331.....	34	9 510 290 093.....	26
0 510 515 005.....	41	0 510 615 341.....	37	0 510 725 352.....	66	9 510 290 094.....	26
0 510 515 007.....	39	0 510 625 013.....	32	0 510 725 353.....	66	9 510 290 095.....	26
0 510 515 011.....	38	0 510 625 014.....	33	0 510 725 361.....	31	9 510 290 096.....	26
0 510 515 012.....	40	0 510 625 015.....	33	0 510 725 363.....	65	9 510 290 097.....	26
0 510 515 013.....	40	0 510 625 016.....	34	0 510 725 364.....	66	9 510 290 098.....	26
0 510 515 015.....	37	0 510 625 017.....	34	0 510 725 377.....	65	9 510 290 099.....	26
0 510 515 018.....	39	0 510 625 022.....	32	0 510 765 012.....	85	9 510 290 100.....	26

Bosch Rexroth Corporation
Mobile Hydraulics
Mobile Controls, Electronics,
and External Gear Units
1700 Old Mansfield Road
Wooster, OH 44691-0394
Telephone (330) 263-3300
Facsimile (330) 263-3330
www.boschrexroth-us.com

© 2006 Bosch Rexroth Corporation
All rights reserved. Neither this document, nor any part of it, may be reproduced,
duplicated, circulated or disseminated, whether by copy, electronic format or any
other means, without the prior consent and authorization of Bosch Rexroth Corp.

The data and illustrations in this brochure/data sheet are intended only to describe
or depict the products. No representation or warranty, either express or implied,
relating to merchantability or fitness for intended use, is given or intended by virtue
of the information contained in this brochure/data sheet. The information contained
in this brochure/data sheet in no way relieves the user of its obligation to insure the
proper use of the products for a specific use or application. All products contained
in this brochure/data sheet are subject to normal wear and tear from usage.

Subject to change.