H M series Order Sheet (Print out this page for sending orders.)

We'll hand in to you a drawing in accordance with your order. The drawing shall be approved before starting in on production.

1) Select one from each spec table d fill blank spaces with "O".

and	i illi blank spaci
	Pulses/Rev.
X	100PPR
æ	25PPR

*25PPR and yet 100 Clicks/Revolution

Pow	ver Supply	Output
	5V	5V (330Ω Pull Up)
	5V	Open Collector
天	5V	(for Line Driver)
	12V	5V(2.2kΩ Pull Up)
	12V	12V(2.2kΩ Pull Up)
	12V	Open Collector
	12V-	for Photocoupler
	24V	(Open Collector)

* Transistor will be "OFF" at every clicked positions.

(For other open collector output models, transistors will be "ON" at every clicked positions.

	Logo on the dial	
	None	
\times	with "TOSOKU" logo	
	with an original logo()_

2-Position Enabling Switch		
\times	None	
	One on the left	
	On both sides	

Emergency Switch (contacts)	
None	
Mounted ()

* 1 for (NO), 4 for (NC) maximum (1A/4B). Maximum of 4 contacts in total (1A3B or 4B).

	Magnet on the backsic	le
X	None	
	Mounted	

Α	xis Selector/Multiplication Selector Switches
\times	MR8C type(Gray code switch)
	MR8A type (Selection switch)

Indicat	ions for Axis Selector (left)
e.g.	OFF, X, Y, Z, 4, 5
\vee	·
Indicat	ions for Multiplication Selector (right)
e.g.	×1, ×10, ×100

	Curl Cord Length
	2m Curl Cord (for only 19-conductor cord)
\times	3m Curl Cord
	4m Curl Cord (for only 19-conductor cord)
	5m Curl Cord

* We will select either 19-conductor cord or 25conductor cord to cover your requested specs

	Waterproofed Connector (for curl cord)
	None
\times	Male connector (EBSP2119MG-D, DDK)
	Female connector (EBSP2119FGS-D, DDK)

* Fill in both spaces to order both connectors.

2) Other options

Other options to request
(e.g.)
Switches with LED illumination x2
2 contact selector switch x1



Rotary Encoders

Pulse Generators
Rotary Switches

Code Switches

•Lever Switches
•Trackballs